



MIGHTY EX6

Refrigerator Body

Engine			
Turbo Charger Intercooler			Allow allowed English
Number of Cylinder		4 stroke-cycle, Water-cooled, Direct-injection diesel Engine 4 in-line	
Piston Displacement (cc)		3.933cc	
ristori bispiacement (ce)		Manual (5 Speed)	Auto (6 Speed)
Max. Power** ps/rpm (kw)	Euro V	140ps/2,500 (102kw) Man	170ps/2,500 (125kw) Auto
Max. Torque ** (nm/rpm)	Euro V	289/1,400 (392nm) Man	448/1,400 (608nm) Auto
Fuel System	Injection pump	Denso Common Rail System	
Transmission		Manual (E Spood)	Auto (4 Spood)
Type Version		Manual (5 Speed) M035 S 5	Auto (6 Speed) Allison 1000x fe
Drive		Single Plate Clutch	Lock up Torque Converter
Park Pawl		N/A	YES
PTO		Preperation for PTO	Preperation for PTO
Permissable Torque		147 nm 2000 Rpm	339 nm (min rpm 1200)
Front Axle			
Туре		Reverse Elliot type " I " beam	
Capacity	kg	2760 kg	
Front Axle		1700.1	
Capacity	kg	4700 kg	
Tyre & Wheel		Single Front Dual Poar	
Type Tyre	Front / Rear	Single Front, Dual Rear 205/75R17.5-10PR	
Wheel	Front / Rear	17.5 x 6.00	
Steering	TTOTIL / TCG	17.5 X 6.66	
Steering		Power Assisted	
3		Adjustable Steering Wheel	
Service Brake			
Front / Rear		Disc/Disc	
Vehicle Dynamic Control (VDC)		(ESC) Electronic Stability Control, (ABS) Anti Brake Skid, (HSA) Hill Start Assist,	
Dealds a Dasta		(ESS) Emergency Stop Signal	
Parking Brake Actuation		Internal expanding type on Propeller sha	ft at the rear of Transmission assembly
Exhaust Brake		internal expanding type on Propeller sna	it at the real of fransinission assembly
Type		Vacuum operated, Butterfly Valve type	
Suspension			
Type	Front / Rear	Semi-elliptic, laminated Leaf Springs	
Shock absorber		Gas telescopic type on the FRONT/REAR	axle
Exhaust system			
General		Horizontal	
Fuel tank		100ℓ	
Capacity		1008	
Frame Type		"H" type frame with channel sectional sig	de rail & cross members, side rail is reinforced with
Main section side rail dimension (mm)	Depth x Flange x Thickness : 183 x 60 x	
Weights		, ,	
*Chassis cab weight kg	Range	SWB 3,950kg, MWB 4,100kg (aprox)	
** Max Gross Vehicle Weight		5,995 kg /6,500 kg	
Gross vehicle weight	Front /Rear	2,760/4,700	
Box Body			
Type		Panel Liner Tuff (anti-moisture)	
Panel			de to 100T), 2x rows Internal F track preparation
Spec			Alloy chequer floor , Drain channel at front
Rear Door		Dual Container style Rear Doors, (optional	
Side Door	CWD (20E0)	LH Side Container Door (width approx 9	
Size m	SWB (2850) MWB (3400)	Internal L 3.4, X W 2.1,x H 1.9 (optional cu Internal L 4.3, X W 2.2,x H 2.1 (optional cu	
Rear bumper	141410 (3400)	Internal E 4.5, A W 2.2, X H 2.1 (optional ci	ustom sizing available)
Refridgeration			max 400 or similar), this is not installed until
<u> </u>			plug in back up, freezer or choices from Carrier
		or Thermoking are possible	•
		- ·	


Electrical system	
Audio	M450 (Radio+Aux/MP3 USB) Multidisplay
Auto Locking	Central Door Locking + Power Window + Keyless Entry + Semi Trim
Steering Wheel Controls	Bluetooth Phone - Audio - Cruise Control
Head lamps	Semi-sealed Beam / Adjustable Dim
Front Combination Lamps	Turn signal / Hazard-Amber, Position - White
Fog Lamps	White
Rear Combination lamps	
	Turn signal / Hazard-Amber, Tail / Stop - Red
License Plate Lamp	White
Service Lamp Circuit	Yes
Daytime Running Lights	Yes
12v Socket in Dash	Yes x2
Power Windows	Yes
Back-up Lamp	White
Instruments	
Meter Cluster	Fixed type
Meter	Speedometer / Tachometer / Fuel gauge / Water temperature gauge LCD with odometer / Trip meter / Clock
Warning Lamps & Indicators	Brake fluid level of reservoir / Parking brake / Oil pressure / Battery charge /
Warriing Lamps & indicators	Tell-tale lights for head light high beam / Turn signals / Door open / Seat belt / Low fuel
Horn	Single, Electric
Cruise Control	Yes
Heating/ Air conditioning (Manual)	Yes
Steering Wheel Audio Remote Control	Yes
Steering Wheel Auto Cruise Control	Yes
Body /Cab	
Type Mounting	Tilt type with torsion bars, all steel welded construction with safety zone design Rigid or Semi floating type
Windshield	One piece type with Laminated glass, Tinted upper section
Windshield Wipers	Dual electric three speed (intermittent / low / fast) wipers & washer
Mirrors	Mirror - Heated
Driver's Seat	Coil Suspension, urethane foam cushioned STD trim
Passenger's seat	Bench seat. STD Trim
Steering Column	Fully Adjustable
	Yes
Roof Marker Lights	
Overhead Storage	Yes
Mirror Width	Narrow STD (optional LONG)
Active Safety Feautures	
Electronic Stability Control	Yes
ABS Braking	Yes
Daytime Running Lights	Yes
Hill Start Assist	Yes
Auto Headlights	Yes
Bluetooth Hands Free	Yes
Heated Mirrors	Yes
Warranty	
Cab Chassis	3 years or 150,000km (whichever occurs first) against manufactures defects
Upper body	According to supplier
Refrigeration (where applicable)	Where applicable any refrigeration supplied will be either from Transcold or Thermo king, all warranty and service:
reingeration (where applicable)	be according to their terms and conditions


Annotations


- 1) Empty vehicle weight and curb weight shown are to 3.5% variation to allow for production tolerance.
- 2) Empty vehicle weight and curb weight include weight of oil, fuel, coolant and spare tire carrier & bracket, but exclude standard tool set
- 3) The vehicle specification may differ per country.
- 4) Hyundai New Zealand reservs the right to alter the specifications, equipment or options or discontinue the models at any time without prior notice.
- *Approximate, depending on variant and specification
- **Max GVW includes the front and rear axle loads based on permissable tyre load 5,995kg & 6,500kg varients
- images may contain additional cost options


MIGHTY EX6

Refrigerator Body









EX6 MWB W/B:3400

Please Note:

- -All drawings are indicative and may show additional cost options
- -All measurements should be viewed as approximate measurements
- -Internal measurements shown are wall to wall or floor to ceiling, door entrances and floor may have a reduced measurement due to construction requirements
- -Refrigeration unit shown is for marketing purposes only (please refer page 2 refrigeration specification for detail)
- -Dimensions shown are a standard specification however build to order custom specifications are available on request